

# Ultima

# **Printer specifications**

300dpi retransfer

#### HoloKote® card security

HoloKote® built-in security watermark is printed across the entire card surface, this feature also exploits the wavelengths of the film to fluoresce under UV lighting conditions. Available with 10 watermarks as standard, any of these watermarks can be replaced with your own customised design or company logo through an easy-to-use, but securely encrypted, online delivery method. HoloKote® printing requires the use of secure dye film (YMCKS).

#### **Encoding security options**

Magnetic stripe: HiCo and LoCo encoder ISO 7811, JIS2. Custom formats: Contact - ISO 7816. EMV contact chip. Contactless: MIFARE®, DESFire®, HiD iClass®, ProX and Legic.

3 years MagiCoverPlus or 250,000 panels limited manufacturer's warranty covering electronic/electrical failure and bad workmanship. A loan printer will be provided should the above situation occur and Technical Support are unable to resolve the problem (UK, EU and

#### **Printer interfaces**

USB 2.0, 10/100 BASE-T Ethernet

#### Compatibility

Windows 7, 8.1, 10 (32 and 64bit) Windows server, 2008, 2012, 2016. GNU/Linux and Mac OS X 10.9.0 upwards.

#### Card capacity

200 card feeder, 200 card stacker. Weight

#### 16.74kg (36.90 lbs).

External power supply 100-240V 50-60Hz autoranging.

334mm L x 458mm W x 431mm H (13.14" L x 18.03" W x 16.96" H).

Colour: up to 100 cards per hour.

#### Operating environment

Sheltered office environment 10°C to 30°C (50°F to 85°F).

### Consumables

#### Part No.

#### Ultima HoloKote® dye film

• Ultima YMCKS Secure HoloKote® dye film, 750 images HE750YMCKS • Ultima YMCKS Secure HoloKote® film set (4 YMCKS and 3 RT films), SET-HE3000S

#### Ultima dye film

- HE1000YMCK • Ultima YMCK dye film, 1000 images • Ultima YMCKK dye film, 750 images HE750YMCKK SET-HE4000
- Ultima 4 x YMCK dye film and 4 x RT film set, 4000 images
- HE1000RT • Ultima retransfer film, 1000 images

#### Cleaning kit

Card sizes: ISO CR80 85.6mm x 54mm / 3.375" x 2.125" Card types: PVC, PET, PC, PVH, ABS. Card thickness: 0.51mm to 1.3mm / 0.020" to 0.050"

#### **Variants**

#### Part No.

E9887

Ultima Uno	
Magicard Ultima: single-sided printer.	3680-0001

Magicard Ultima Duo: double-sided printer.

#### 3680-0021

# Card security options







A standard security watermark printed across the entire card surface. The Ultima HoloKote® features 10 standard designs.





#### Custom HoloKote®

A fully flexible and customisable secure watermark printed across the entire card







#### Magnetic stripe

The Ultima can be specified with ISO standard 7811 or JIS2 compatible HiCo encoding of magnetic stripe cards.





#### Smart card encoding

Smart card encoding options: Contact chip, Mifare®, Desfire®, iClass®,



\*Warranty subject to the observance of specific conditions of use and maintenance, as well as the use of certified 'Original Magicard' dye films.

Magicard and Ultima are trademarks or registered trademarks of Magicard Ltd.

All other trademarks, brand names, or product names belong to their respective holders.

The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation







**MAGICARD** 

# Ultima

Photo-quality over-the-edge retransfer printing



# Ultima



Powered by a high-grade processing unit with an impressive array of features, Ultima is ideal for the localised or centralised issue of high-volumes of secure smart cards.

An intuitive touch screen, with print preview and supplies indicators, provides an easy-to-use interface to Magicard's most advanced and durable print engine.

Ultima enables you to print up to 100 high definition full colour cards per hour. The quality of print means staff can quickly and easily identify the facial features on ID cards for comparison against the holder. This makes it the ideal solution for drivers' licences, national ID cards and other cards where security is paramount.

The Ultima retransfer printer comes with built-in visual security via the use of up to 10 secure HoloKote® watermarks. That means that if you choose to do so, you can distinguish different departments with a separate holographic design. For additional built-in security, Ultima exploits the wavelengths of the dye-film so it can fluoresce under UV lighting.

High capacity consumables (1000 prints) and hoppers, combined with a range of encoding options to write secure electronic data to the card, make the Ultima ideal for high volume localised or centralised issuance of secure smart cards.



Choose from 10 patterns of fluorescent Secure HoloKote®

# Printer highlights













#### Standard features













# Optional features











## High-quality reverse transfer card printing

The key to the Magicard Ultima is the reverse transfer (also called retransfer) printing process. Unlike the standard dye sublimation process, your card design is first printed on a clear film and that film is then adhered to the card surface.

This process gives you a higher definition print quality and allows you to print successfully even on smart cards with uneven surfaces. It also gives you additional card durability and tamper-resistance so the cards will last longer.

# Features an intuitive touch screen

## Secure ID cards with Magicard HoloKote®

As with all Magicard printers, the Ultima comes with the built-in HoloKote® system and prints a secure watermark across the face of every card at no additional cost – the first reverse transfer printer to offer this.

New with the Ultima, you can now print a Secure HoloKote® – a fluorescent version of the HoloKote® watermark that will show up under black light, adding another layer of security to your cards. Choose from 10 standard patterns of Secure HoloKote®, printed using the specialised YMCKS secure colour ribbon.

### **Printer variants**

Single-sided		Double-sided	
Ultima Uno	3680-0001	Ultima Duo	3680-0021

